

EcoTank M1180



DATASHEET / BROCHURE



With 11,000 pages' worth of ink, Wi-Fi, USB and Ethernet connectivity, this EcoTank is easy-to-use with a low TCO.

Wi-Fi-enabled mono EcoTank printer for business, with an extremely low TCO in a user-friendly, stylish and compact design. Print up to an amazing 11,000 pages with the included ink that comes in a bottle for mess-free, easy refills. Wi-Fi, USB and Ethernet connectivity, PCL support, and a fast FPOT of six seconds all help to keep productivity high.

Save money

A high ink yield combined with Epson's economical inkjet technology delivers a low TCO and a competitive cost per page.

Save time

This reliable cartridge-free printer features an enhanced ink filling system and easy-to-use ink bottles, keeping intervention to a minimum. Thanks to the ink tank being positioned at the front of the printer, with a clear view of the ink levels, this new design is compact and provides easy access for refilling. Its fast First Page Out Time (FPOT) of six seconds from sleep, and 20ppm print speed, mean you won't be waiting around for jobs.

Save energy

Unlike a laser, our inkjet technology doesn't need any heat during the printing process, helping to keep energy use low and reduce electricity bills.

Connectivity

Wi-Fi, Ethernet and USB connectivity and a compact footprint mean that it's easy to place on a desktop and connect to a user's PC or laptop.

KEY FEATURES

- **Low TCO and energy use**
Keep your printing costs extremely low
- **High ink yields**
Print up to 11,000 pages with the included ink
- **Save time**
Fast FPOT
- **Built for business**
Duplex printing and PCL support
- **Easy connectivity**
Wi-Fi, USB and Ethernet

PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	PrecisionCore™ TFP print head
Nozzle Configuration	400 Nozzles Black
Minimum Droplet Size	2,8 pl
Ink Technology	Pigment ink
Category	Home Office, Office Desktop, Office Workgroup
All-in-One Functions	Print

PRINT

First Page Out	Monochrome 6 Seconds
Printing Speed ISO/IEC 24734	20 pages/min Monochrome
Duplex Printing Speed ISO/IEC 24734	9 A4 Pages/min Monochrome
Maximum Printing Speed	39 pages/min Monochrome (plain paper 75 g/m ²)
Printing Resolution	1.200 x 2.400 DPI
Printing Volume	5.000 pages per month
	The maximum number of printed pages per month based on the performance capabilities of the printer, including ISO rated print speeds and paper handling capabilities.
Recommended Duty Cycle	200 - 1.500 pages per month
Colours	Black

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

CONNECTIVITY

Network Printing Protocols	IPP, LDP, Port 9100, WSD
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNT, SLP, WSD, LLTD, Ping
Interfaces	Hi-Speed USB - compatible with USB 2.0 specification, Ethernet interface (100 Base-TX / 10 Base-T), Wi-Fi Direct, Wireless LAN IEEE 802.11b/g/n
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES)
Network Protocol	TCP/IPv4, TCP/IPv6

PAPER / MEDIA HANDLING

Paper Formats	A4 (21.0x29.7 cm), Legal, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B5, B6, C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter
Compatible Paper Weight	64 g/m ² - 90 g/m ²
Duplex	Yes (A4, plain paper)
Output Tray Capacity	100 Sheets
Paper Tray Capacity	250 Sheets Standard, 250 Sheets Maximum
Standard paper tray(s)	250-sheet paper tray
Maximum paper input	250
Rear paper path (special media)	Yes
Number of paper trays	1

EcoTank M1180

WHAT'S IN THE BOX

- Printer
- X2 ink bottles
- Warranty document
- Power cable

PRODUCT SPECIFICATIONS

GENERAL	
Recommended number of users	From: 1 To: 3
Energy Use	0,8 Watt (sleep mode), 14 Watt (Printing), 3,4 Watt (Ready), 2 Watt (Power off), TEC 0,13 kWh/week
Product dimensions	375 x 347 x 151 mm (Width x Depth x Height)
Product weight	4,3 kg
Noise Level	6,9 B (A) according to ISO 7779 pattern with Epson Premium Glossy Photo Paper / Photo RPM mode - 56 dB (A) according to ISO 9296
Compatible Operating Systems	Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP SP3 or later (32-bit), XP Professional x64 Edition SP2
Sound Power Noise	Operation: 6,9 B (A) Operation: 56 dB (A)
Mobile and Cloud printing services	Epson Connect (iPrint, Email Print, Remote Print Driver), Google Cloud Print
Power supply	220V, 240V
OTHER FEATURES	
Emulations	PCL5e, PCL6
OTHER	
Warranty	12 months Carry in, 100.000 pages

SUPPLIES

● 110 EcoTank Pigment black ink bottle	C13T03P14A	6.000 pages
● 110S EcoTank Pigment black ink bottle	C13T01L14A	2.000 pages
● Maintenance Box	C13T04D100	

LOGISTICS INFORMATION

SKU	C11CG94404SA
EAN code	8715946655338
Country of Origin	Philippines
Layer	2 Units

EcoTank M1180

INK YIELD DATA



110S Mono ink bottle 110S



2.000 pages*

* Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 19752. 11,000 pages yield based on two ink bottles included with this printer. 6,000 pages yield based on EcoTank ET-MX1XX Series Black Bottle XL ink bottle sold separately. Quoted yields are NOT based on ISO/IEC24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature.



EPSON[®]